

Cryltek Mat

PAINT

MACHINE OR MANUAL APPLICATION

INTERIOR APPLICATION



DESCRIPTION

Cryltek Matt is a semi-thick matt paint. It is used as an opacifying primer layer.

USE

Ideal for printing / undercoat on plasterboard, or standard substrates of bare buildings or adherent paint coatings in good condition.

TECHNICAL SPECIFICATIONS



TYPICAL SPREADABILITY

7 to 8 m² / l depending on substrate type.



DENSITY

1,65 kg/l



SOLID CONTENT

- Solid content by mass: 67%
- Solid content by volume: 45%



APPLICATION CONDITIONS

- +8°C to +35°C
- Max. relative humidity 70%



PH

8 +/- 1



CLEANING TOOLS

With water



DRYING

- In dust free environment in 30 minutes.
- Dry to touch in 1 hr.
- Can be top coated in 4 hrs.

CHARACTERISTICS

- Easy to apply.
- Finish when dry: matt
- Beautiful whiteness
- Excellent adhesive properties
- Rapid drying, can be painted over on the same day.
- Classification: group I, class 7b2 as per AFNOR NF T 36-005.

PACKAGING AND STORAGE

- 25 kg plastic bucket.
- Shelf life is 1 year in unopened original packaging, protected from frost and extreme heat.

ENVIRONMENTAL INFORMATION

- EU limit value for this product (cat. A/a): 30 g/l (2010). This product contains max. of 2 g/l VOC.
- Indoor Air Emission Class

METHOD OF APPLICATION

SUBSTRATES:

- Plaster, gypsum tiles, plasterboard.
- Concrete, cement plaster, fibro cement, old acrylic paintwork.
- Previously patterned plaster.

PREPARATION OF SUBSTRATE:

• The substrates, preparatory work and application conditions must be compliant with applicable building trade regulations (e.g. DTU) and standards.

APPLICATION TIPS:

- Airless spraying machine: size 517 airless nozzles Applied in criss-cross pattern.
- Brush, roller.
- Dilute with 2% water if required.
- 10% dilution for patterning on plasterboard.

HEALTH AND SAFETY

The safety information sheet is available from:
www.icp-alltek.com/en-gb/documentation/