

# Alltek Aquafibre

READY MIXED DECORATIVE PLASTER

MANUAL OR MACHINE APPLICATION

INTERIOR APPLICATION



## DESCRIPTION

Alltek Aquafibre is a traditional antistatic, peelable cellulose-based coating for machine or manual application.

## USE

- Decorative coating for interiors, walls and ceilings on all standard substrates, with textured, stippled or brushed surfaces.
- May be waxed.

## TECHNICAL SPECIFICATIONS

**X/m<sup>2</sup>** TYPICAL SPREADABILITY  
2 to 3 kg/m<sup>2</sup> per layer depending on smoothness of substrate.

**g/l** DENSITY  
1.7 +/- 0,1 kg/l

**Es** SOLID CONTENT  
• Solid content by mass: 54%  
• Solid content by volume: 22%

**°C** APPLICATION CONDITIONS  
• +8°C to +35°C  
• Max. relative humidity 70%

**pH** PH  
8 +/- 1

**Water** CLEANING TOOLS  
With water

**h** DRYING  
• 12 to 36 h on average, depending on application thickness, temperature, ventilation, humidity and substrate type. Sanding and recoating: after complete drying.

## CHARACTERISTICS

- Ready to use plaster
- Paintable with pastel paints
- Fire rating: A2-s1, d0 as per European standard EN 13501-1.
- Classification: group III class 2 as per AFNOR NF T 36-005, in compliance with standard AFNOR NF T 30-608.

## PACKAGING AND STORAGE

- 25 kg plastic bucket.
- Shelf life is 1 year in unopened original packaging, protected from frost and extreme heat.

## ENVIRONMENTAL INFORMATION

- VOC content: < 1 g/l.

- Indoor Air Emission Class



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

## METHOD OF APPLICATION

- SUBSTRATES:**
- On powdery substrates, apply a fixative.
  - Plaster, gypsum blocks, plasterboard, cement rendering, old walls, old paintwork, grainy wood.

- PREPARATION OF SUBSTRATE:**
- The substrates, preparatory work and application conditions must be compliant with applicable building trade regulations (e.g. DTU) and standards.

- APPLICATION TIPS:**
- Stir before use if necessary.
  - Filling knife, trowel.
  - Can be applied with spraying machine, 4-6 or 8mm nozzles.

- RECOMMENDATIONS:**
- Ensure adequate ventilation to remove excess moisture and accelerate drying.

## HEALTH AND SAFETY

The safety information sheet is available from:  
[www.icp-alltek.com/en-gb/documentation/](http://www.icp-alltek.com/en-gb/documentation/)