

# Alltek Granifibre G

READY MIXED DECORATIVE PLASTER

MANUAL OR MACHINE APPLICATION

INTERIOR APPLICATION



## DESCRIPTION

Alltek Granifibre G is a grainy decorative interior surfacing for machine application. Interspersed with small marble grains, it will mask small irregularities in the substrate.

Alltek Granifibre G is white with a matt finish.

## USE

Plaster for interiors, walls and ceilings on all standard substrates.

## TECHNICAL SPECIFICATIONS



### TYPICAL SPREADABILITY

0.7 to 1 kg/m<sup>2</sup> according to desired finish.



### DENSITY

1.7 +/- 0,1 kg/l



### SOLID CONTENT

- Solid content by mass: 71%
- Solid content by volume: 51%



### APPLICATION CONDITIONS

- +8°C to +35°C
- Max. relative humidity 70%



### PH

8 +/- 1



### CLEANING TOOLS

With water



### DRYING

- 24 h on average, depending on application thickness, temperature, ventilation, humidity and substrate type. Sanding and recoating: after complete drying.



### RECOMMENDED THICKNESSES

- Min. thickness: 0.3 mm
- Max. thickness: 2 mm

## CHARACTERISTICS

- Ready to use paste
- Conceals flaws
- Smooth after drying
- Fire rating: A2-s1, d0 as per European standard EN 13501-1.
- Classification: group III class 2 as per AFNOR NF T 36-005, in compliance with the standard AFNOR NF T 30-608

## PACKAGING AND STORAGE

- 25 kg plastic bucket.
- Shelf life is 1 year in unopened original packaging, protected from frost and extreme heat.

## ENVIRONMENTAL INFORMATION

- VOC content: < 1 g/l.



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

- Indoor Air Emission Class

## METHOD OF APPLICATION

### SUBSTRATES:

- On powdery substrates, apply a fixative. Plaster, gypsum blocks, plasterboard, cement rendering, old walls, old paintwork, grainy wood.

### PREPARATION OF SUBSTRATE:

- The substrates, preparatory work and application conditions must be compliant with applicable building trade regulations (e.g. DTU) and standards.

### APPLICATION TIPS:

- Stir before use if necessary.
- Can be applied with spraying machine, pressure pots, gravity spray gun.

### RECOMMENDATIONS:

- Ensure adequate ventilation to remove excess moisture and accelerate drying.

## HEALTH AND SAFETY

The safety information sheet is available from:  
[www.icp-alltek.com/en-gb/documentation/](http://www.icp-alltek.com/en-gb/documentation/)