

Alltek Cachet Blanc

READY MIXED PLASTER

MANUAL OR MACHINE APPLICATION

INTERIOR APPLICATION



DESCRIPTION

Alltek Cachet Blanc is a ready-for-use beige plaster, with fillers (sand), organic binders and additives (preservatives and rust inhibitor).

USE

- Plaster for interiors, walls and ceilings on all standard substrates.
- Alltek Cachet Blanc, especially formulated to have good adhesive properties on all standard substrates and very low shrinkage, can be applied very thickly while relatively fine. Recommended as finishing coat before paint over Alltek Cachet Bleu Lissage ZN.

TECHNICAL SPECIFICATIONS

X/m² **TYPICAL SPREADABILITY**
0.7 to 1.5 kg/m² per layer depending on smoothness of substrate.

D **DENSITY**
1,7 +/- 0,1 kg/l

Es **SOLID CONTENT**
• Solid content by mass: 78%
• Solid content by volume: 63%

A **APPLICATION CONDITIONS**
• +8°C to +35°C
• Max. relative humidity 70%

pH **PH**
8 +/- 1

C **CLEANING TOOLS**
With water

🕒 **DRYING**
• 24 h on average, depending on application thickness, temperature, ventilation, humidity and substrate type. Sanding and recoating: after complete drying.

📏 **RECOMMENDED THICKNESSES**
• Min. thickness: 0,4 mm
• Max. thickness: 1,5 mm

CHARACTERISTICS

- Ready to use.
- Easy to apply.
- Outstanding filling and finish.
- Excellent adhesive properties.
- Very good spreading power.
- Easily sanded.
- Fire rating: A2-s1, d0 as per European standard EN 13501-1.
- Classification: group III class 2 as per the standard AFNOR NF T 36-005, in compliance with the standard AFNOR NF T 30-608

PACKAGING AND STORAGE

- 25kg plastic bag with handle
- Shelf life is 1 year in unopened original packaging, protected from frost and extreme heat.

ENVIRONMENTAL INFORMATION

- VOC content: < 2 g/l.

Indoor Air Emission Class



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

METHOD OF APPLICATION

- SUBSTRATES:**
- Poured concrete, rough concrete.
 - Terracotta bricks and tiles, plaster, gypsum blocks, plasterboard.
 - Wood and wood products, old painted substrates in good condition

PREPARATION OF SUBSTRATE:

- The substrates, preparatory work and application conditions must be compliant with applicable building trade regulations (e.g. DTU) and standards.

- APPLICATION TIPS:**
- Stir before use if necessary.
 - Spraying machine nozzle 4 to 8 mm, depending on condition of substrate and equipment used (follow the manufacturer's advice).
 - Smoothing blades of all sizes.
 - Sanding with grain size 100 to 150.

RECOMMENDATIONS:

- Ensure adequate ventilation to remove excess moisture and accelerate drying.

HEALTH AND SAFETY

The safety information sheet is available from:
www.icp-alltek.com/en-gb/documentation/